

# eikon<sup>™</sup> e2



e2



### Standard Features

- Advanced Cooking Technology<sup>®</sup> with planar plume and microwave technologies for faster, even heating and browning
- "Ventless\* Cooking" capabilities through built-in catalytic converter with full protein capabilities

Project: Item: Quantity:

Approval

- Ability to use a standard metal baking pan while in convection/microwave mode
- Automatic voltage detection (U.S. only)
- Up to ten (10) times faster than conventional cooking methods
- Power management system keeps power below
  18 amps
- Quiet operation maximum noise level of 59 dBA in idle mode

\*Local codes prevail. These are the "authority having jurisdiction" as stated by the National Fire Protection Association, Inc., in NFPA96-1994.


## Specifications

#### Construction

- 430 stainless steel casework and 304 stainless steel interior cavity
- Easily removable and cleanable grease and cooling air filters

#### EasyToUCH<sup>™</sup> Control Panel

- Icon driven, color touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power settings and user instructions for each stage
- Self diagnostics capability to monitor components
- Easy menu updates or data transfer via USB memory stick
- Multi-languages available



(Front view)

The e2 utilizes a new and patented heat transfer method called "planar plumes". Heated air is directed into planes which collide above the food surface and are then drawn around the food.



Merrychef USA 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888-417-5462 Fax: 800-285-9511 E-Mail: info@merrychefusa.com www.merrychefusa.com



Model


e2

## *∽ Merrychef*

Overall Size		
Height (on 4" legs)	27"	686 mm
Width	14.75″	375 mm
Depth (overall without handle)	28.5″	724 mm
Depth (door open 90 degrees)	40.25″	1022 mm
Weight	150 lbs.	68 kg
Oven Cavity Dimensions		
Height	9.6″	244 mm
Width	9.6″	244 mm
Depth	12"	305 mm
Wall Clearance		
Тор	2″	50.8 mm
Sides	2″	50.8 mm
Electrical Specifications		
Phase	1 ph	
Voltage	208 / 240	
Frequency	60Hz	
Amperage Requirement	20 amp	
Plug	NEMA 6-20P	
Cord Length	6′	G
Max Power Rate	4015W	
Power Output (Microwave)	1000W	
Power Output (Heater)	2200W	

Specifications		
Control System	easyToUCH <sup>™</sup> , iconic symbo touch screen control pane	
Cooking Stages	6	
Total Cooking Programs	1024	
Maximum Cooking Time	60 Min	
Defrost	No	
Microwave Distribution System	Rotating Active Antennae	
Magnetron(s)	1	
Display	LCD Backlit	
Interior Light	No	
Automatic Voltage Sensor	Yes	
USB & Menu Updates Software	Yes	
Temperature Range	212-527°F (100-275°C)	
Temperature Increments	1°F	
Air Filter	Yes - Air & grease	
Fan Speed	0-100%	
Fan Speed Increments	10%	
Microwave Power	10-100%	
Microwave Power Increments	10%	
Rack Option	No	
Rack Positions	1	
Turntable	No	
Stackable	No	
Warranty	1 year parts and labor	
Accessories in Box	_	
Operator Manual/Cleaning Instructions	1 Unit	
Cool Down Tray	1 Unit	
USB Menu Key	1 Unit	
Bottle Cleaner	1 Unit	
Bottle Guard	1 Unit	
Trigger Sprays	2 Units	

Model 🛛 e2



Merrychef USA 1111 N. Hadley Rd. Ft. Wayne, IN 46804 Tel: 888-417-5462 Fax: 800-285-9511 E-Mail: info@merrychefusa.com www.merrychefusa.com © 2012 Merrychef USA 01/12

