



BakerTop™



XAB985PL



	XAB985PL
Capacity	16 18"x26" Full Sheet Pans
Pitch	2 -11/16" (67 mm)
Frequency	60 Hz
Voltage	208V 3~/240V 3~
Electrical power	29,3 kW / 38,4 kW
Dimensions	34-1/4" (869 mm) x 38-1/4" (972 mm) x 73-15/32" (1866 mm)
Weight	404 lbs (183 kg)



BakerTop™





ELECTRIC

BAKING MODES

- Convection baking 86 °F - 500 °F
- Mixed steam and convection baking 118 °F - 500 °F, with STEAM.Maxi™ 30% to 90%
- Mixed humidity and convection baking 118 °F - 500 °F, with STEAM.Maxi™ 10% to 20%
- Steaming 118 °F - 266 °F with STEAM.Maxi™ technology 100%
- Dry air baking 86 °F - 500 °F with DRY.Maxi™ technology settable 10% to 100%
- Maximum pre-heating temperature 572 °F
- Core probe
- Delta T baking with core probe
- MULTI.Point core probe
- SOUSS-VIDE core probe
- MULTI.Time: technology to manage up to 9 timers to bake at the same time different products

AIR DISTRIBUTION IN THE BAKING CHAMBER

- AIR.Maxi™ technology: multiple fans with reversing gear
- AIR.Maxi™ technology: 3 air speeds, programmable
- AIR.Maxi™ technology: 3 semi static baking modes, programmable
- AIR.Maxi™ technology: pulse function

CLIMA MANAGEMENT IN THE BAKING CHAMBER

- DRY.Maxi™ technology: high performance moist and humidity extraction, programmable by the user
- DRY.Maxi™ technology: baking with humidity extraction 86 °F - 500 °F
- STEAM.Maxi™ technology: steaming 118 °F - 266 °F
- STEAM.Maxi™ technology: combination of moist air and dry air 118 °F - 500 °F
- ADAPTIVE.Clima technology: cavity humidity measurement and regulation
- ADAPTIVE.Clima technology: repeatability of the baking process through the memorization of the real baking process
- ADAPTIVE.Clima technology: 20 ADAPTIVE.Clima process memory

THERMAL INSULATION AND SAFETY

- Protek.SAFE™ technology: maximum thermal efficiency and working safety (cold door glass and external surfaces)
- Protek.SAFE™ technology: fan impeller brake to contain energy loss at door opening
- Protek.SAFE™ technology: electrical power absorption related to the real needs
- Protek.SAFE™ technology: gas power absorption related to the real needs

AUTOMATIC CLEANING

- Rotor.KLEAN™ XC405: 3 automatic and 2 semi-automatic washing programs

PATENTED DOOR

- Door hinges made of highly durable and self-lubricating technopolymer
- Reversible door, even after the installation
- Door docking positions at 60°-120°-180°

AUXILIARIES FUNCTIONS

- 99 baking programs memory, each one capable of 9 baking steps
- Possibility to assign a name to the stored programs
- Preheating temperature up to 572 °F settable by the user
- Display of the residual baking time (when baking not using the core probe)
- Holding baking mode «HOLD»
- Continuous functioning «INF»
- Display of the set and real values of time, core probe temperature, cavity temperature and humidity
- «COOL» function for rapid cavity cooling
- Temperature unit °C or °F

TECHNICAL DETAILS

- Rounded stainless steel (DIN 1.4301) cavity for sanitation and ease of cleaning

Cavity lighting through external LED lights	.
Steam proof sealed BakerTouch control panel	.
High-durability carbon fibre door lock	.
Door drip pan with continuous drainage, even when the door is open	.
High capacity appliance drip pan connectable to appliance drain	.
Light weight – heavy duty structure using innovative materials	.
Proximity door contact switch	.
2-stage safety door lock	o
Self-diagnostic system	.
Safety temperature switch	.
Accessible internal glass to simplify the door cleaning	.
Stainless steel C-shaped rack rails with notched recesses for easy loading	.