

BUNN®

12 Cup Automatic Coffee Brewer with 2 Warmers

ITEM#

PROJECT

DATE



Model OL (2 warmers)

(decanters sold separately)

Dimensions: 23.5" H x 12" W x 18.5" D

Features

12 Cup Automatic Coffee Brewer

- Brews 5.1 to 7.5 gallons (19.3 to 28.4 litres) of perfect coffee per hour.
- All stainless steel construction.
- Can also be operated as a pourover unit.
- Designed to function well in low or uneven water pressure situations.
- Faucet kit available.
- SplashGard® funnel deflects hot liquids away from the hand.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12⁷/₁₆" H x 2¹/₂" W x 3" D

31.6 cm H x 6.35 cm W x 7.62 cm D



Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000

Dimensions: 4¹/₄" Base x 2³/₄" Sidewall

10.8 cm Base x 6.98 cm Sidewall



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001*

RWS1 Product No. : 12203.0010

*Also available with side handles
or black decor.



Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

20.95 cm H x 5.87 cm Dia.

Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in
quantities of 2, 3, 6, 12, & 24)



Easy Pour® orange decanter (for decaf)

Product No. : 06101.0101

Quantity: 1 (also packaged in
quantities of 2, 3, 6, 12, & 24)



Model

OL20

OL35

Agency Listing



Patents Apply

10/09

A1.13

Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
OL 20	20820.0001	120	17	1800	2050	5.1 gal./hr.	4.9	34 lbs.	No
OL 35	20820.0002	120/240	16.6	3500	3750	7.5 gal./hr.	4.9	34 lbs.	No

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

*Power cord (NEMA 5-15P) 15 Amp-120V machine only.

Electrical: OL 20 requires 2-wires plus ground service rated 120V, single phase, 60Hz.

OL 35 requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60Hz.

Plumbing: 10-90 psi (138-621 kPa). Supplied with 1/4" male flare fitting.

