

CAPACITY CHARTS

CUBERS

MODEL FAMILY	MAX. ICE PROD. LBS. PER 24 HOURS @		CONDENSING UNIT	VOLTAGE
	70°F AIR 50°F WATER	90°F AIR 70°F WATER		
ICEU 060	69	54	AIR	115
ICEU 150	175	139	AIR/WATER	115
ICEU 220	260	220	AIR/WATER	115
ICEU 300	356	296	AIR/WATER	115
ICE 0250	352	284	AIR/WATER	115
ICE 0320	355	312	AIR/WATER	115
ICE 0400	528	449	AIR/WATER	115
ICE 0500	625	499	AIR/WATER/REMOTE	115
ICE 0520	528	441	AIR/WATER	115
ICE 0606	727	590	AIR/WATER/REMOTE	208-230
ICE 0806	1094	840	AIR/WATER/REMOTE	208-230
ICE 1006	1201	941	AIR/WATER/REMOTE	208-230*
ICE 1406	1466	1187	AIR/WATER/REMOTE	208-230*
ICE 1506	1431	1202	REMOTE	208-230
ICE 1806	1891	1468	WATER/REMOTE	208-230*
ICE 2106	2202	1855	WATER/REMOTE	208-230*

*AVAILABLE IN THREE-PHASE

FLAKERS

MODEL FAMILY	MAX. ICE PROD. LBS. PER 24 HOURS @		CONDENSING UNIT	VOLTAGE
	70°F AIR 50°F WATER	APPLICATION BIN STORAGE*		
EMF 450	552	N/A	AIR/WATER	115
EMF 800	852	N/A	AIR/WATER	115
EMF 1106	1152	N/A	AIR/WATER/REMOTE	208-230
EMF 2306	2624	N/A	AIR/WATER/REMOTE	208-230
EF 250	400	143	AIR	115
EF 450	472	213		
		143	AIR	115
		213		
		315		
EF 800	772	213	AIR	115
		315		

BINS

MODEL NUMBER	APPLICATION BIN STORAGE*	ARI BIN STORAGE **
CRT 125	94	74
ICEU 060	28	25
ICEU 150	100	74
ICEU 220	100	74
ICEU 300	130	112
B 25	255	190
B 40	365	270
B 42	374	275
B 55	556	400
B 75	740	580
B 100	927	670
B 120	1193	896
B 150	1499	1135
B 170	1866	1417

DISPENSERS

MODEL NUMBER	APPLICATION BIN STORAGE *	ARI BIN STORAGE **
CD 40022		120
CD 40030		180
CD 40130		180
CD 40230		180
IOD 150	150	
IOD 200	200	
IOD 250	250	
EFD 270	12	

NOTE: EFD 270 produces 273 lbs. of ICE per day

*Application bin storage rated in pounds at volume x 90% of internal volume x 34 lbs. per cubic foot

**ARI bin storage rated in pounds per ARI Standard 820