MOFFET E311MS Half Size Electric Convection Oven



Commercial construction



Stainless steel outer




Stainless steel door with full viewing window

Stay cool heavy duty stainless steel door handle



4 half pan capacity

- 60 minute bake timer
- S hour roast timer
- Cook n hold system
- Insulated porcelain inner
- Internal lighting
- Water injected steam (hook-up optional)





E311MS



Order Toll Free 1800 551 8795

E311MS

Unit shall be a Moffat electrically heated Turbofan convection oven E.T.L listed (UL Std 197) and NSF listed (NSF-4). The oven shall have a one piece vitreous porcelain enamel oven liner, stainless steel top and sides with single stainless steel door and full viewing window. Oven liner shall be insulated on all sides and have capacity for four half size sheet pans. A single speed fan shall evenly circulate air internally.

The oven shall be controlled by a mechanical thermostat with a range from 150°F to 525°F, have a broil switch built into the thermostat, a 60 minute bake timer, 3 hour cook n hold timer, push button water injection and oven light switch. Oven shall be able to be bench mounted on 4" legs or on Moffat's A25 stand. Oven shall be fitted with a NEMA 6-15P cordset.

MOFFAT E311MS Half Size Electric Convection Oven

CONSTRUCTION

Stainless steel top and sides Porcelain oven interior Toughened twin pane door glass Strong and stylish door handle 4 half pan capacity (wire racks included) Fully insulated Stainless steel control panel with overlay Fully enclosed motor at rear

CONTROLS

On/off switch Mechanical thermostat, variable between 150°E to 525°E 3 hour roast timer Cook n hold factory preset at 158°F (range 140°F to 194°F) Water injection steam (momentary switch) Low velocity fan system Broil position for cheesemelting/toasting Oven light

CLEANING AND SERVICING

Fully removable racks and fan baffle Fully removable bottom element guard Easy clean surfaces Access to all controls from front panel No tools required to replace lamps Removable gaskets - no tools required

OPTIONS

Stand with casters Half size sheet pans

SPECIFICATIONS

Electrical requirements 208V, 60Hz, 1P+N+E, 2.9kW,14.0A

220-240V, 60Hz, 1P+N+E, 3.1kW, 13.0A NEMA 6-15P cordset fitted

Water 3/4" thread



80psi max inlet pressure 20psi min inlet pressure

External Dimensions

Width	31 ³ /8" (796mm)
Height	22 ⁷ /8" (567mm)
Depth	23 ⁵ /8" (600mm)

Internal Dimensions

Width	21 ¹ /2" (544mm)
Height	16 ¹ /2" (418mm)
Depth	15 ¹ /8" (385mm)

Oven Rack Dimensions		
Width	20 ⁷ /8" (530mm)	
Depth	14 ¹ /2" (370mm)	

Nett Weight 189lbs (86kg)

Packing Data

227lbs	(103kg)
14.5ft ³	(0.41m ³)
Width	32 ⁷ /8" (835mm)
Height	28 ¹ /2" (720mm)
Depth	27 ¹ /4" (690mm)

Clearances

Left side	1″	(25mm)
Right side	1″	(25mm)
Rear	1″	(25mm)
Тор	8″	(200mm)

MOFFAT.

www.moffat.com

U.S.A

Moffat Inc 3765 Champion Boulevard Winston-Salem North Carolina 27105 Call Free 1800 551 8795 Ph 336-661 0257 Fax 336-661 9546 Email sales@moffat.com www.moffat.com

Canada

Serve Canada 22 Ashwarren Road Downview Ontario, M3J 1Z5 Ph 416-631 0601 Fax 416-631 0315 Email info@servecanada.com

Australia

Moffat Pty Limited 740 Springvale Rd Mulgrave Victoria 3170 Australia Ph 03-9518 3888 Fax 03-9518 3833 Email vsales@moffat.com.au www.moffat.com.au

New Zealand

Moffat Limited 16 Osborne St PO Box 10-001 Christchurch New Zealand Ph 03-389 1007 Fax 03-389 1276 Email sales@moffat.co.nz www.moffat.co.nz

United Kingdom

Blue Seal Limited Units 6-7 Mount St Business Park Birmingham B7 5QU England Ph 0121-327 5575 Fax 0121-327 9711 Email sales@blue-seal.co.uk www.blue-seal.co.uk

