

Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

# Appia 2 Group Spec Sheet

### Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

#### Water Softening Equipment

- 1. Water Softener Capacity: Single 4400 gpg
- Water Softener Capacity: Double 8800 gpg 2.
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable

□ Water Softener/Maintenance Calculation

5. Water Softener Capacity: Manual - 4400 gpg

#### Power Requirements

- Volts: 220 (voltage range of 208-240)
- Watts: 3400
- Amp draw: 17
- Receptacle: 6-20



#### NSF / ANSI Std.4

Nema 6-20

The average water consumption of this machine is 4 gallons per day, which represents 128 drinks at 4oz per drink.


Gallon Capacity **Days Until Cartridge** Cartridge Grain Water Hardness Gallons of Water ÷ Capacity (grains per gallon) of Cartridge Used per Day Needs to be Replaced

## □ Counter Space Requirements

- Height: 21 inches
- Depth: 22 inches
- Width: 31 inches

Fax:

- Weight: 160 pounds
- Drain Requirements Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.



- □ Shipping Dimensions & Weight
- Height: 27 inches
- Depth: 25 inches
- Width: 34 inches
- Weight: 175 pounds



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation.

Signature:

Customer Name:

Company Name: \_\_\_\_

Phone:

Email: