

FFAR10MED2



56.75" x 23.63" x 23.5" (H x W x D)

10.1 cu.ft. upright auto defrost medical/scientific all-refrigerator with digital thermostat and NIST calibrated thermometer/alarm; includes front lock, hospital grade cord, and internal fan

Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Assembled in the USA from domestic and imported components

Product Features:

Reliable temperature stability	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines
Factory installed lock	Keyed lock conveniently located towards the top of the door for added security (2 keys included)
Automatic defrost	Reduced maintenance with auto defrost system
Internal fan	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety in high traffic areas

FFAR10MED2 Specifications:

Overview	
Height of Cabinet	56.75" (144 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	45.5" (116 cm)
Capacity	10.1 cu.ft. (286 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Other Energy Info	120 Volts / 60 Hz.
Amps	1.5
Weight	140.0 lbs. (64 kg)
Shipping Weight	145.0 lbs. (66 kg)
Estimated Time to Ship	5 to 7 days
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	3.0oz.
High Side PSI	285.0
Low Side PSI	70.0
Level Legs Qty	2
Interior Light	Yes
Temperature Range	2°C to 8°C
Dimensions	
Interior Height	48.25" (123 cm)
Interior Width	20.5" (52 cm)
Interior Depth	17.75" (45 cm)

Compressor Step Height	6.25" (16 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.5" (14 cm)

