

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item#:	Qty:
Available W/H :	
Approval:	

## Solid Door Freezer

Reach-In Bottom Mount Super Deluxe Series

Model: TSF-23SD

### \_\_\_FEATURES / BENEFITS =\_\_

#### ■ DIGITAL TEMPERATURE CONTROL SYSTEM

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

#### ■ HIGH-TECH MONITOR

The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the freezer. You can easily change the temperature by adjusting the thermostat

#### ■ STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel top, bottom and back). It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury. The Super Deluxe can add a touch of style to the most refined setting.

#### ■ STURDY, CLEAN STAINLESS STEEL SHELVING

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

#### ■ LEFT HINGED MODEL AVAILABLE

#### ■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

#### ■ AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the freezer door opens, the circulation of hot, moist air into the freezer is prevented. This increases energy efficiency and lengthens the life of the compressor.

#### ■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing and stay open door features make this the ultimate choice in customer convenience.

#### ■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

#### **■ BOTTOM MOUNT COMPRESSOR UNITS**

Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.

3 YEAR PARTS & LABOR WARRANTY



FREEZER HOLDS - 10°F ~ 0°F FOR THE BEST IN FROZEN FOOD PRESERVATION











ENERGY STAR® Qualified

Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TSF-23SD	1	23	3	1/2	7.8	293	27 x 303/8 x 781/4

# Solid Door Freezer

## Model: TSF-23SD

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA-5-15P				
Full Load Amperes	7.8				
Compressor HP	1/2				
Feed Wires with Ground	3				
Cord Length ft.	9				
Refrigerant	R-404A				
DIMENSIONAL DATA					
# of Doors	1				
# of Racks Accepted	1				
Net Capacity cu. ft.	23				
Ext. Length Overall in.	27 (686mm)				
Ext. Depth Overall in.	303/8 (770mm)				
Ext. Height Overall in.*	78 <sub>1/4</sub> (1987mm)				
Int. Length Overall in.	23 (584mm)				
Int. Depth Overall in.	261/4 (666mm)				
Int. Height Overall in.	603/8 (1534mm)				
Gross Weight lbs.	293				
# of Shelves	3				
Shelf Size (LxD) in.	215/8 x 231/4				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

## ■ WARRANTY: 3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**


- SAFETY SHIELDED INCANDESCENT INTERIOR LIGHTING
- MINIMUM WATTAGE HEATER IN CABINET FRAME
- Door Locks Standard
- Positive Seal Self-Closing Doors
- EASY REPLACEABLE ONE PIECE MAGNETIC DOOR GASKETS
- SELF-CONTAINED SYSTEM
- STANDARD 4" SWIVEL CASTERS WITH LOCKS ON THE FRONT SET
- SOLID AND STURDY GRILLE DESIGN
- COMES STANDARD WITH HIGH TEMPERATURE AUDIBLE ALARM
- Low Profile Casters Available (Optional)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- FULL AND HALF PAN RACKS AVAILABLE (OPTIONAL)
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE


#### ■ OPTIONAL ACCESSORIES:

- ☐ 5" Diameter swivel casters
- ☐ 6" Standard legs
- □ Additional stainless steel shelves
- □ Additional PE coated wire shelves
- ☐ Half door bun tray racks. Each holds up to seven 18"Lx26"D sheet pans (sold separately)
- ☐ Full door bun tray racks. Each holds up to fifteen 18"Lx26"D sheet pans (sold separately)

Ver.201401

#### **PLAN VIEW** (unit: inch)

















**ENERGY STAR®** Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519













<sup>\*</sup> Height does not include 5" caster height or 6" optional legs.