BACK MOUNT SANDWICH PREP. TABLES

Back Mounted Condensing Unit

EPBN - Series • EPBNR1 • EPBNR2 • EPBNR2 • EPBNR2 • EPBNR3













Cabinet Construction

Heavy duty stainless steel interior and exterior, galvanized steel finished bottom and back wall of exterior. High quality 16 gauge stainless steel worktop, top lid and hood. 2.5" thick high density foamed-in-place polyurethane insulation. Four 4" diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build-up.

Refrigeration System

- · Back mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Slide-out condensing unit for convenient repair and maintenance
- Front air breathing for built-in applications
- Environmentally friendly CFC free R-134A refrigerant
- · Air defrost controlled by electrical timer
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pressure relief port for rapid cabinet re-entry
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

Doors

- · Heavy duty stainless steel interior and exterior
- 2.5" thick high density foamed-in-place polyurethane insulation
- · Rounded corners for a sleek and modern appearance
- Heavy duty adjustable torsion spring self-closing system
- One piece snap-in magnetic door gaskets for easy replacement
- Heavy duty recessed door handles for a flat surface

Preparation Area

- 1/2" thick foam insulated lids to prevent moisture build-up and heat exchange
- Removable and adjustable sanitary 12 1/4" deep cutting board
- Sanitary polycarbonate pans

Shelving

- One epoxy coated wire shelf per section
- Stainless steel pilasters and shelf clips

Temperature Control

- Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- Easy to set analog thermostat



BACK MOUNT SANDWICH PREP. TABLES

1 1/8"-

1/6


Back Mounted Condensing Unit




EPBN - Series • EPBNR1 • EPBNR2 • EPBNR2 • EPBNR2 • EPBNR3

www.EVERESTref.com


SIDE VIEW 31 1/2" 12 1/4" 12 1/4" 13 1/2"




‡1 1/8"




▲ EPBNSR2






59 1/2"

1/4





22 3/4" 22 3/4"	-	29 3/4"	43 1/4"
▲ EPBNR2	<u></u>	ਹੂ 🗼	<u> </u>

▲ EPB	NWR2	 	

43 1/4" 34 3/4" 29 3/4"

Model	Ref/ Frz/	# of Doors	Capacity (Cu.Ft.)	НР	Refrigerant	# of Shelves	# of	Power (V-Hz-Ph)	Crated Amps Weight					* Height does not
	Dual	סוטטו	(Gu.Ft.)		· ·	Sileives	Pans	(V-HZ-PII)		(LBS)	L	D	H*	include 5" for casters
EPBNR1	Ref	1	6.5	1/6	R-134A	1	1/6 X 6	115-60-1	4.00	216	27 1/2	31 1/2	38 1/4	Ref = Refrigerator Frz = Freezer Dual = Ref & Frz Combo
EPBNSR2	Ref	2	8.5	1/6	R-134A	2	1/6 X 8	115-60-1	4.20	258	35 1/2	31 1/2	38 1/4	Budi - Hor a Fiz dombo
EPBNR2	Ref	2	11.8	1/4	R-134A	2	1/6 X 12	115-60-1	4.20	319	47 1/2	31 1/2	38 1/4	
EPBNWR2	Ref	2	15	1/3	R-134A	2	1/6 x 12 1/4 x 2	115-60-1	5.01	373	59 1/2	31 1/2	38 1/4	
EPBNR3	Ref	3	18.3	1/3	R-134A	3	1/6 X 18	115-60-1	5.20	438	71	31 1/2	38 1/4	

Disclaimer: Product dimensions are for general purposes and not absolute value. Slight variations may exist. If dimensions are critical, please contact Everest.

