DRAWERED UNDERCOUNTER REFRIGERATORS

Back Mounted Condensing Unit

ETB - Series

• ETBR1-D2 • ETBSR2-D2 • ETBR2-D4 • ETBWR2-D4 • ETBR3-D2













ETBR3-D2

Cabinet Construction

Heavy duty stainless steel interior and exterior, with galvanized steel finished bottom and back wall of exterior. High quality 16 gauge stainless steel worktop, ABS evaporator drain cover. 2.5" thick high density foamed-in-place polyure-thane insulation. Four 4"diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build-up.

Refrigeration System

- · Back mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Slide-out condensing unit for convenient repair and maintenance
- Front air breathing for built-in applications
- · Environmentally friendly CFC free R-134A refrigerant
- Air defrost controlled by electrical timer
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pressure relief port for rapid cabinet re-entry
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

Doors & Drawers

- · Heavy duty stainless steel interior and exterior
- 2.5" thick foamed-in-place polyurethane insulation
- Rounded corners for a sleek and modern appearance
- Heavy duty adjustable torsion spring self-closing door system
- One piece snap-in magnetic door and drawer gaskets for easy replacement
- Heavy duty recessed door and drawer handles for a flat surface
- Heavy duty 304 stainless steel drawer frames with low-friction ball bearing slides (Note: refer to the website for pan configurations)

Shelving (Model ETBR3-D2)

- Two epoxy coated wire shelves
- Stainless steel pilasters and shelf clips

Temperature Control

- Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- · Easy to set analog thermostat

Option

• 4" high stainless steel backsplash for worktop use

DRAWERED UNDERCOUNTER REFRIGERATORS


Back Mounted Condensing Unit




• ETBR1-D2 • ETBSR2-D2 • ETBR2-D4 • ETBWR2-D4 • ETBR3-D2





Dimensions






31 1/2"






22 3/4"

34 3/4" 29 3/4"



59 1/2"



FΤ	۲R	R2	_D	14

22 3/4'

▲ ETBWR2-D4

▲ ETBR3-D2

Model	Frz/ Door	טטטוס מ	ors & Capacity		Refrigerant (# of a	Power	Amps	Crated Weight (LBS)	Exterior Dimensions (Inches)			* Height does not
		Drawers					Pans	(V-Hz-Ph)			L	D	Н*	include 5" for casters a
ETBR1-D2	Ref	2(DR)	5.6	1/6	R-134A	N/A	1/2 x 4 1/4 x 2	115-60-1	4.10	200	27 1/2	31 1/2	29 3/4	Drawer pans are not included
ETBSR2-D2	Ref	2(DR)	7.5	1/6	R-134A	N/A	1/2x4, 1/3x1 1/4x2, 1/6 x1	115-60-1	4.40	234	35 1/2	31 1/2	29 3/4	Ref = Refrigerator Frz = Freezer
ETBR2-D4	Ref	4(DR)	10.3	1/6	R-134A	N/A	1/2x4, 1/3x4 1/4x2, 1/6x2	115-60-1	4.40	291	47 1/2	31 1/2	29 3/4	Dual = Ref & Frz Combo D = Door
ETBWR2-D4	Ref	4(DR)	15	1/4	R-134A	N/A	1/2x4, 1/3x8 1/4x2, 1/6x4	115-60-1	4.70	347	59 1/2	31 1/2	29 3/4	DR = Drawer
ETBR3-D2	Ref	1(D) 2(DR)	18.3	1/3	R-134A	2	1/2x2, 1/3x8 1/4x1, 1/6x4	115-60-1	5.20	373	71	31 1/2	29 3/4	

Disclaimer: Product dimensions are for general purposes and not absolute value. Slight variations may exist. If dimensions are critical, please contact Everest.

