

SIDE MOUNT UNDERCOUNTER REFRIGERATORS

Side Mounted Condensing Unit



EVEREST
REFRIGERATION

www.EVERESTref.com

SIDE MOUNT UNDERCOUNTER REFRIGERATORS (SIDE MOUNT)

ET – Series

• ETR1 • ETR2 • ETWR2 • ETR3



ETR1



ETR2



ETWR2



ETR3

Cabinet Construction

Heavy duty stainless steel interior and exterior, with galvanized steel finished bottom and back wall of exterior. High quality 16 gauge stainless steel worktop, ABS evaporator drain cover. 2.5" thick high density foamed-in-place polyurethane insulation. Four 4" diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build-up.

Refrigeration System

- Side mounted condensing unit for extra interior space compared to back mounted units
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Removable condenser coil air filter for easy cleaning
- Environmentally friendly CFC free R-134A refrigerant
- Air defrost, time initiated and terminated
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pressure relief port for rapid cabinet re-entry
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

Doors

- Heavy duty stainless steel interior and exterior
- 2.5" thick foamed-in-place polyurethane insulation
- Rounded corners for a sleek and modern appearance
- Heavy duty adjustable torsion spring self-closing door system
- One piece snap-in magnetic door gaskets for easy replacement
- Heavy duty recessed door handles for a flat surface
- All 2015 and newer models come standard with door locks

Lighting

- Shielded incandescent interior lighting

Shelving

- Two epoxy coated wire shelves per section
- Stainless steel pilasters and shelf clips

Temperature Control

- Factory preset temperature, 35°F
- Setting temperature range from 33°F to 54°F
- Easy to read digital temperature display
- Easy to program push button temperature control
- Microchip digital control and monitoring system with a variety of functions to monitor and maintain optimum temperature

Option


- 4" high stainless steel backsplash for worktop use

• Project / Customer _____

• Item No. _____

• Model No. _____

Warranty

 **5 Year — Compressor Warranty**
3 Year — Parts & Labor Warranty
Applicable to units purchased after July 1, 2014.

Contact

 201 W. Artesia Blvd, Compton, CA 90220
T. (310) 323-6586, (800) 444-6285
F. (310) 323-7524, (310) 761-1127

SIDE MOUNT UNDERCOUNTER REFRIGERATORS

Side Mounted Condensing Unit






EVEREST
REFRIGERATION

www.EVERESTref.com



ET – Series

• ETR1 • ETR2 • ETWR2 • ETR3



Dimensions





▲ ETR1



▲ ETR2



▲ ETWR2



▲ ETR3

Model	Ref/ Frz/ Dual	# of Doors	Capacity (Cu.Ft.)	HP	Refrigerant	# of Shelves	Power (V-Hz-Ph)	Amps	Crated Weight (LBS)	Exterior Dimensions (Inches)			* Height does not include 5" for casters Ref = Refrigerator Frz = Freezer Dual = Ref & Frz Combo
										L	D	H *	
ETR1	Ref	1	9	1/4	R-134A	2	115-60-1	2.94	223	35 1/2	31 1/2	29 1/2	
ETR2	Ref	2	13	1/4	R-134A	4	115-60-1	2.94	256	47 1/2	31 1/2	29 1/2	
ETWR2	Ref	2	18	1/4	R-134A	4	115-60-1	2.94	306	59 1/2	31 1/2	29 1/2	
ETR3	Ref	3	22	1/3	R-134A	6	115-60-1	5.20	348	71	31 1/2	29 1/2	

Disclaimer: Product dimensions are for general purposes and not absolute value. Slight variations may exist. If dimensions are critical, please contact Everest.